

Solid, Single End Bus Wire

Bare Cu Part Number	Tinned Cu Part Number	AWG	Nom. Diameter*	Nom. CMA	Feet Per Pound
SBC-8	STC-8	8	0.129"	16510	20.01
SBC-10	STC-10	10	0.102"	10380	31.82
SBC-12	STC-12	12	0.080"	6530	50.6
SBC-14	STC-14	14	0.064"	4107	80.4
SBC-16	STC-16	16	0.051"	2583	128
SBC-18	STC-18	18	0.040"	1624	204
SBC-20	STC-20	20	0.032"	1022	324
SBC-22	STC-22	22	0.025"	642	515
SBC-24	STC-24	24	0.020"	404	818
SBC-26	STC-26	26	0.016"	254	1,300
SBC-28	STC-28	28	0.013"	160	2,070
SBC-30	STC-30	30	0.010"	101	3,290
SBC-32	STC-32	32	0.008"	63	5,227
SBC-34	STC-34	34	0.006"	40	8,310
SBC-36	STC-36	36	0.005"	25	13,210

Specifications:

Soft annealed copper wire, Alloy CDA 110.
 Meets ASTM-B-3 for Bare Cu
 and ASTM-B-33 for Tinned Copper wire.

Standard Reel Sizes:

- 5 lb.
- 10 lb.
- 35 lb.
- 70 lb.

Notes:

All bus wire is put up on standard
 NON-RETURNABLE packaging.

Ph: 607-674-2030
Fx: 607-674-9367

Hamilton Products, Inc.

Email: info@hamprods.com