

Nickel Plated Copper Flat Braids

HP Part Number	AA59569A	Nominal Flat Width	Construction	AWG Equivalent	Nom CMA	Nom Amps*
9223	F36N0031	3/64"	24-1-36	22	600	7
9225	F36N0062	3/32"	24-2-36	19	1200	11
9229	F36N0078	1/8"	24-3-36	18	1800	16
9229/1	F36N0109	5/32"	24-4-36	16	2400	19
9230	F36N0125	3/16"	24-5-36	15	3000	25
9231	F36N0171	1/4"	24-7-36	14	4200	32
9231/1	F36N0156	1/4"	24-10-36	12	6000	40
9231/2	F36N0203	9/32"	24-13-36	11	7800	46
9233	F36N0375	5/8"	48-8-36	10	9600	53
9233/1	F36N0500	5/8"	48-11-36	9	13200	62
9234	F36N0781	3/4"	48-18-36	7	21600	85
9240	F30N0437	1/2"	24-10-30	6	24000	93
9242	F30N0500	5/8"	24-15-30	5	36000	120
9262	F30N0875	1 3/8"	48-7-30	5	33600	100
9268	F30N1375	1 1/2"	48-11-30	3	52800	145

Specifications:

Braided with a specific number of ends of tinned copper wire per ASTM-B-355, to the construction below, then mill-rolled to the specified width and thickness.