

Nickel Plated Copper Tubular Braids

HP Part Number	AA59569A	Nominal Flat Width	Construction	AWG Equivalent	Nom CMA	Nom Amps*
9110	R32N0062	1/16"	16-1-32	20	1024	9
9112	R32N0109	7/64"	16-2-32	17	2048	18
9114	R32N0125	1/8"	24-2-32	15	3072	25
9116	R32N0171	11/64"	24-3-32	14	4608	32
9118	R32N0203	13/64"	24-5-32	11	7680	46
9120	R32N0375	3/8"	48-3-32	11	9216	46
9122	R32N0500	1/2"	48-4-32	9	12288	62
9124	R32N0781	25/32"	48-7-32	7	21504	88
9132	R34N0062	1/16"	16-2-34	19	1270.4	11
9134	R34N0109	7/64"	16-4-34	16	2540.8	19
9136	R34N0125	1/8"	24-3-34	16	2858.4	19
9137	-	9/64"	24-4-34	15	3811.2	26
9138	R34N0171	11/64"	24-5-34	14	4764	32
9140	-	3/16"	24-6-34	13	5716.8	38
9142	-	1/4"	24-7-34	12	6669.6	41
9144	-	3/8"	24-8-34	11	7622.4	46
9145	R34N0375	3/8"	48-5-34	10	9528	53
9146	R34N0500	1/2"	48-7-34	9	13339.2	62
9148	-	5/8"	48-8-34	8	15244.8	64
9150	-	11/16"	48-10-34	7	19056	81
9152	R34N0781	25/32"	48-11-34	7	20961.6	85
9153	-	13/16"	48-12-34	7	22867.2	90
9160	R36N0031	1/32"	24-1-36	22	600	7
9162	R36N0062	1/16"	24-2-36	19	1200	11
9163	R36N0078	5/64"	24-3-36	18	1800	16
9164	R36N0109	7/64"	24-4-36	16	2400	19
9166	R36N0125	1/8"	24-5-36	15	3000	25
9167	R36N0156	5/32"	24-10-36	12	6000	40
9168	R36N0171	11/64"	24-7-36	14	4200	32
9170	R34N0203	13/64"	24-8-34	11	7622.4	46
6170/1	R36N0203	13/64"	24-13-36	11	7800	46
9171	R36N0250	1/4"	24-16-36	10	9600	53
9171/1	R30N0281	9/32"	24-5-30	9	12000	60
9171/2	R30N0375	3/8"	24-7-30	8	16800	75
9172	R36N0375	3/8"	48-8-36	10	9600	53
9173	R30N0437	7/16"	24-10-30	6	24000	90
9173/1	R30N0500	1/2"	24-15-30	5	36000	120
9174	R36N0500	1/2"	48-11-36	9	13200	62
9175	R30N0562	9/16"	48-10-30	3	48000	145
9175/1	R30N0656	21/32"	48-16-30	1	76800	190
9176	R36N0781	25/32"	48-18-36	7	21600	88
9176/1	-	7/8"	48-19-36	7	22800	93
9177	R30N0875	7/8"	48-7-30	5	33600	100
9178	R30N1000	1"	48-8-30	4	38400	120
9179	R30N1125	1 1/8"	48-9-30	4	43200	130
9180	R30N1250	1 1/4"	48-10-30	3	48000	145
9181	R30N1375	1 3/8"	48-11-30	3	52800	145
9182	R30N1500	1 1/2"	48-12-30	3	57600	145
9183	R30N2000	2"	48-14-30	2	67200	180
9184	-	2 1/4"	48-16-30	1	76800	190

Specifications:

Braided with a specific number of ends of tinned copper wire per ASTM-B-355, to the construction below, then mill-rolled to the specified width and thickness.