

Silver Plated Copper Flat Braids

Specifications: Braided with a specific number of ends of tinned copper wire per ASTM-B-298, to the construction below, then mill-rolled to the specified width and thickness.

| HP Part Number | AA59569A | Nominal Flat Width | Construction | AWG Equivalent | Nom CMA | Nom Amps* |
|----------------|----------|--------------------|--------------|----------------|---------|-----------|
| 7223 | F36S0031 | 3/64" | 24-1-36 | 22 | 600 | 7 |
| 7225 | F36S0062 | 3/32" | 24-2-36 | 19 | 1200 | 11 |
| 7229 | F36S0078 | 1/8" | 24-3-36 | 18 | 1800 | 16 |
| 7229/1 | F36S0109 | 5/32" | 24-4-36 | 16 | 2400 | 19 |
| 7230 | F36S0125 | 3/16" | 24-5-36 | 15 | 3000 | 25 |
| 7231 | F36S0171 | 1/4" | 24-7-36 | 14 | 4200 | 32 |
| 7231/1 | F36S0156 | 1/4" | 24-10-36 | 12 | 6000 | 40 |
| 7231/2 | F36S0203 | 9/32" | 24-13-36 | 11 | 7800 | 46 |
| 7233 | F36S0375 | 5/8" | 48-8-36 | 10 | 9600 | 53 |
| 7233/1 | F36S0500 | 5/8" | 48-11-36 | 9 | 13200 | 62 |
| 7234 | F36S0781 | 3/4" | 48-18-36 | 7 | 21600 | 85 |
| 7240 | F30S0437 | 1/2" | 24-10-30 | 6 | 24000 | 93 |
| 7242 | F30S0500 | 5/8" | 24-15-30 | 5 | 36000 | 120 |
| 7262 | F30S0875 | 1 3/8" | 48-7-30 | 5 | 33600 | 100 |
| 7268 | F30S1375 | 1 1/2" | 48-11-30 | 3 | 52800 | 145 |