

Tinned Copper Flat Braids

Specifications: Braided with a specific number of ends of tinned copper wire per ASTM-B-33, to the construction below, then mill-rolled to the specified width and thickness.

HP Part Number	AA59569A	Nominal Flat Width	Construction	AWG Equivalent	Nom CMA	Nom Amps*
6221	-	.025"	8/1/1936	27	200	4
6222	-	1/32"	16-1-36	24	400	6
6223	F36T0031	3/64"	24-1-36	22	600	7
6224	-	3/32"	16-3-36	19	1200	11
6225	F36T0062	3/32"	24-2-36	19	1200	11
6226	-	7/64"	16-4-36	18	1600	16
6229	F36T0078	1/8"	24-3-36	18	1800	16
6229/1	F36T0109	5/32"	24-4-36	16	2400	19
6230	F36T0125	3/16"	24-5-36	15	3000	25
6231	F36T0171	1/4"	24-7-36	14	4200	32
6231/1	F36T0156	1/4"	24-10-36	12	6000	40
6231/2	F36T0203	9/32"	24-13-36	11	7800	46
6232	-	3/8"	48-6-36	12	7200	60
6232/1	-	3/8"	24-5-30	9	12000	40
6233	F36T0375	5/8"	48-8-36	10	9600	53
6233/1	F36T0500	5/8"	48-11-36	9	13200	62
6233/2	-	1/2"	48-8-36	10	9600	53
6234	F36T0781	3/4"	48-18-36	7	21600	85
6235	-	1"	48-18-36	7	21600	85
6236	-	13/16"	48-19-36	7	22800	93
6236/1	-	7/8"	48-22-36	6	26400	105
6237	-	3/4"	24-67-36	4	40200	125
6238	-	1 5/8"	48-84-36	1	100800	230
6240	F30T0437	1/2"	24-10-30	6	24000	93
6242	F30T0500	5/8"	24-15-30	5	36000	120
6244	-	3/4"	24-20-30	3	48000	145
6246	-	7/8"	24-24-30	3	57600	165
6248	-	15/16"	24-26-30	2	62400	170
6250	-	15/16"	24-27-30	2	64800	175
6252	-	1"	24-32-30	1	76800	195
6260	-	3/4"	48-5-30	6	24000	93
6262	F30T0875	1 3/8"	48-7-30	5	33600	100
6264	-	1"	48-8-30	4	38400	120
6266	-	1 1/4"	48-10-30	3	48000	145
6268	F30T1375	1 1/2"	48-11-30	3	52800	145
6270	-	7/8"	48-12-30	2	57600	150
6272	-	1 3/8"	48-14-30	2	67200	165
6274	-	1 1/2"	48-16-30	1	76800	180
6276	-	1 5/8"	48-18-30	1	86400	200
6278	-	1 3/8"	48-22-30	1/0	105600	235
6279	-	1 3/4"	48-26-30	2/0	124800	250
6280	-	2"	48-28-30	2/0	134400	255
6282	-	2"	48-32-30	3/0	153600	290
6284	-	2 1/4"	48-35-30	3/0	168000	320
6286	-	2 3/8"	48-44-30	4/0	211200	370
6287	-	3"	48-47-30	4/0	225600	390
6288	-	2 1/2"	48-52-30	1 250 MCM	249600	410